

National Parks & Wildlife Service

Moneybeg and Clareisland Bogs SAC (Site code 002340)



Raised Bog Restoration Plan (Report)

Version 2a

April 2023

Contents

| | | |
|----------|---|-----------|
| 1 | INTRODUCTION | 1 |
| 1.1 | PURPOSE OF THE RESTORATION PLAN..... | 1 |
| 1.2 | MONEYBEG AND CLAREISLAND BOGS SAC | 1 |
| 1.3 | SITE-SPECIFIC CONSERVATION OBJECTIVES | 2 |
| 2 | RESTORATION MEASURES AT MONEYBEG AND CLAREISLAND BOGS SAC..... | 3 |
| 2.1 | INTRODUCTION | 3 |
| 2.2 | BLOCKING OF HIGH BOG DRAINS | 3 |
| 2.3 | BLOCKING OF DRAINS ON CUTOVER BOG | 4 |
| 2.4 | CONTOUR BUNDING | 6 |
| 2.5 | CELL BUNDING | 7 |
| 2.6 | GENERAL SITE MANAGEMENT | 8 |
| 3 | DRAINAGE MANAGEMENT PLAN | 8 |
| 4 | COMMUNITY BENEFITS | 9 |
| 5 | RESTORATION PLAN IMPLEMENTATION | 9 |
| 5.1 | PREPARATORY | 9 |
| 5.2 | PROGRESS TO DATE | 10 |
| 6 | REFERENCES | 13 |
| | GLOSSARY & ACRONYMS | 14 |

Maps:

| | |
|--|-----------|
| Map 1 - Moneybeg and Clareisland Bogs SAC Boundary | 11 |
| Map 2 - Moneybeg and Clareisland Bogs SAC Restoration Proposals | 12 |

1 Introduction

1.1 Purpose of the Restoration Plan

This restoration plan has been developed by National Parks and Wildlife Service (NPWS) of the Department of Housing, Local Government and Heritage to set out proposals for restoration of raised bog and associated habitats at Moneybeg and Clareisland Bogs Special Area of Conservation (SAC) (002340). This plan identifies technically feasible restoration measures for the various zones of the bog including the high bog, cutover bog and surrounding margins and provides details of progress on implementation of their restoration plans.

The restoration measures set out will enable nature conservation targets for Active Raised Bog (ARB) at this SAC to be met. Although the focus of the restoration plan is on ARB habitat, it is anticipated that restoration measures will also benefit other peatland habitats and can contribute to socio-economic benefits for the local community, improvements to biodiversity and reduced carbon emissions. Monitoring of this restoration plan will be undertaken to ensure that the intended restoration measures are successfully contributing to the achievement of the site-specific targets for ARB at Moneybeg and Clareisland Bogs SAC.

Action 1.1: Develop restoration plan further in partnership with stakeholders.

This plan will be developed further in conjunction with stakeholders to ensure that restoration is carried out in such a way that the conservation requirements of the site can be met, whilst minimising any impacts on adjacent land and maximising benefits to the local community. The plan will develop and change over time through input from stakeholders and will be considered a living document. The primary aim of this restoration plan is to ensure site-specific conservation objectives for Moneybeg and Clareisland Bog SAC can be met.

Section 2 of the restoration plan sets out the restoration measures that have been proposed for Moneybeg and Clareisland Bogs. Section 3 outlines how a drainage management plan for Moneybeg and Clareisland Bogs has been developed as part of this restoration plan. Section 4 describes potential for community benefits to be explored and section 5 outlines progress with implementation of the plan.

Map 1 outlines the location and extent of Moneybeg and Clareisland Bogs SAC. Map 2 illustrates the restoration measures that have been implemented to date as well as any proposed/outstanding restoration measures to be implemented at Moneybeg and Clareisland Bogs.

This document provides an outline of the restoration plan but is supported by detailed datasets that are available on the NPWS Restoration Maps Viewer. This map viewer provides NPWS with an up-to-date view of all restoration plan details and supporting information including status of landowner investigations, landowner consent, progress with construction and details of proposed and remaining restoration measures.

1.2 Moneybeg and Clareisland Bogs SAC

Moneybeg and Clareisland Bogs SAC is situated on the border of Counties Meath and Westmeath, 9 km east of the town of Granard. The SAC includes the raised bog and surrounding areas which include cutover bog, forestry, small areas of wet and improved grassland and scrub and bog woodland on cutover. The SAC consists of two separate lowland raised bogs at Moneybeg and Clareisland, situated on the south and south-west shores of Lough Sheelin. An important feature of these bogs is that in some areas the transition from high bog to open water is intact and not separated by cutover bog as is the case in the majority of other Irish raised bogs.

The SAC has been selected for three Annex I habitats. These are:

- [7110] Active raised bogs*
- [7120] Degraded raised bogs still capable of natural regeneration
- [7150] Depressions on peat substrates of the *Rhynchosporion*

*Priority habitats

This restoration plan has been developed to address restoration measures for these peatland habitats.

The high bog at Moneybeg consists of a single small dome with extensive cutover areas to the east and west. Overall, the high bog is flat, with slopes associated with the southern margin. The local road from Mount Nugent to Finnea runs through the bog and an isolated northern section adjoins the lake shore. There is also a large mineral mound adjoining the western extent of the high bog. The raised bog is surrounded by agricultural land, which in the east slopes steeply down to the cutover. There was conifer forestry to the south and south-west which has been recently clear felled as part of a Coillte EU Life restoration project.

The raised bog at Clareisland consists of a small, linear high bog extending along the shore of Lough Sheelin with only limited cutover areas to the east and west. There is an extensive wet area with frequent pools on the high bog and there is a slight slope towards the semi-natural lake margin. The local road described above runs by the southern margin of the high bog and there is conifer forestry on cutover south of the road. Recent peat cutting has been reported from Moneybeg and Clareisland Bogs SAC.

The Moneybeg and Clareisland Bogs are of considerable conservation significance as it comprises two raised bogs with remnant semi-natural lake margins. The bogs are located at the north-eastern extreme of the range of raised bogs in Ireland.

1.3 Site-specific conservation objectives

Detailed site-specific conservation objectives (SSCOs) aim to define the conditions necessary to maintain or achieve the favourable conservation condition of a habitat or species at site level. The maintenance of habitats and species within sites at favourable condition will contribute to the maintenance of favourable conservation status of those habitats and species at a national level.

A conservation objective has been set for Moneybeg and Clareisland Bogs SAC for ARB habitat using attributes and targets based on parameters set out in the Habitats Directive. In summary, one of the key targets is to restore the area of ARB to 31.7 ha. The area of ARB was reported as 5.3 ha during the latest monitoring survey (2015) and it has been determined that there is potential for 14.8 ha of Degraded Raised Bog (DRB) to be restored to ARB on the high bog following restoration measures. There is also long-term potential for 11.6 ha of bog peat-forming habitats (BPFH) to develop if restoration measures are undertaken on cutover areas. Several targets have been set for other attributes relating to the quality and condition of ARB habitat, including a target to restore adequate transitional areas to support/protect the active raised bog and the ecosystem services it provides. The restoration measures proposed by this restoration plan aim to achieve these targets. Further information on the SSCO's can be found in the Moneybeg and Clareisland Bogs SAC conservation objectives document (NPWS, 2015a) and the conservation objectives supporting document – raised bog habitats (NPWS, 2015b).

2 Restoration measures at Moneybeg and Clareisland Bogs SAC

2.1 Introduction

Hydrological processes are key drivers of raised bog ecology, as raised bogs are predominately fed by precipitation. For ARB to develop or be maintained, mean water levels need to be near or at the bog's surface for most of the year. Seasonal fluctuations should not exceed 20cm below ground surface, and water levels in the peat should be within 10cm of the surface, except for very short periods of time (Kelly & Schouten 2002). Gentle slopes that limit intermittent lateral losses of water (through surface run-off) and encourage sustained water-logging are the most favourable to achieve these conditions. These conditions may be maintained on steeper slopes in areas of focused flow (flushes) (Mackin et al., 2017a; Regan et al., 2020). However, it will not be possible to raise the water level to high enough levels across the entire high bog surface, particularly approaching marginal areas, to enable ARB to develop. Even in high bog areas that do not have potential for ARB to form, water levels should be raised as necessary to support habitat for the areas where ARB can occur.

The main aim of restoration on raised bogs is to maintain or improve the quality of existing areas of ARB or improve the hydrological conditions that will allow ARB to develop in areas with suitable topographic conditions (gentle slopes and/or areas of focused flow). This requires measures to be implemented on both the high bog and cutover areas. Measures implemented on selected areas of cutover will also help to minimise the impact that drainage and cutting has had on the hydrological integrity of the high bog and support a diversity of other transitional wetland habitats (e.g., wet woodland and fen), as well as the species they sustain. Once restored, these transitional cutover zones may provide further ecosystem services through flood attenuation and water supply maintenance and purification, increased carbon sequestration and improvements to the site's overall biodiversity value.

The main restoration measures that may be considered for improving hydrological conditions on raised bogs include:

- Drain blocking (includes drains on both high bog and the margins)
- Removal of forestry/tree clearance
- Installation of marginal dams
- High bog excavation/re-profiling
- Inoculation with *Sphagnum* species
- Bunding on high bog or cutover bog

Further details on each of these measures can be found in Irish Wildlife Manual No. 99 'Best practice in raised bog restoration in Ireland' (Mackin et al., 2017b). Additional measures may be considered in particular instances where there are specific problems that are causing damage to an SAC. The most relevant restoration measures for Moneybeg and Clareisland Bogs SAC are outlined in Section 2.2 – 2.7 below.

2.2 Blocking of high bog drains

Blocking high bog drains slows the flow of water off the surface of the bog and increases the water table in the peat. Drain blocking is a proven and effective restoration measure on Irish raised bogs with minimal maintenance requirements. The approach has been demonstrated at a number of raised bogs in Ireland with very positive results evident in less than 10 years (**Figure 2.1**) as outlined by Fernandez *et al.* (2014).

Sometimes, there are concerns from local communities living close to raised bogs that drain blocking

on the high bog will result in, or exacerbate, flooding. Blocking high bog drains, in fact, slows the flow of water off the bog potentially reducing the frequency and magnitude of flood events by restoring the hydrological function of the bog. To address these concerns NPWS have developed a drainage management plan for Moneybeg and Clareisland Bogs, with further details of this plan outlined within section 3.



Figure 2.1 Example of a peat dam to block a typical high bog drain

Action 2.1: Block high bog drains within Moneybeg and Clareisland Bogs SAC.

There is an extensive network of drains on Moneybeg and Clareisland Bogs, particularly on Moneybeg Bog. It is proposed that all unblocked drains on the high bog are blocked with peat dams. Details of the locations of unblocked drains on the high bog can be found in Map 3.

2.3 Blocking of drains on cutover bog

Blocking of cutover drains slows the flow of water off the cutover areas and increases the water table in the surrounding peat. This can help to reduce the rate of infiltration through the high bog and can lead to conditions that allow peat to form on the cutover (**Figure 2.2**).

Drain blocking on cutover areas has been carried out at a number of raised bogs in Ireland to date resulting in the development of peat-forming vegetation on cutover areas. As with blocking of high bog drains, there are sometimes concerns from local communities living close to raised bogs that drain blocking on cutover bog will result in, or exacerbate, flooding. Blocking drains on cutover bog can slow the rate at which water is lost from the bog therefore potentially reducing the frequency and magnitude of downstream flood events. This restoration measure is primarily focused on former

spread-grounds and only in very rare occasions, where it is absolutely essential, includes agricultural land. Drains in these areas will only be blocked in agreement with landowners and where there is a suitable hydrological barrier such as a functional drain to prevent impacts outside of the restoration area.



Figure 2.2 Water table at the surface of cutover bog following successful drain blocking resulting in *Sphagnum* development less than 10 years after drain blocking (this was previously an area of bare peat)

Action 2.2: Block drains on selected cutover areas within Moneybeg and Clareisland Bogs SAC.

There are several cutover areas surrounding the bog where blocking of drains may reduce ongoing subsidence of the high bog. In some areas this will also lead to the development of peat forming habitats. It is proposed that these drains are blocked, primarily with peat dams, with some plastic reinforcements where necessary to prevent erosion. The required conditions are for the water table to be maintained at or close to the surface, therefore large areas of standing water or deep pools are not desired. Details of the locations on the cutover where it is proposed to block drains can be found in Map 3.

2.4 Contour bunding

Contour bunds on the high bog aims to reduce the rate of lateral flow through the upper layers of the peat. In contrast to some other bunding techniques, contour bunding is not intended as a means of impounding surface water. This method involves excavating a trench 1.5-2.0m deep, re-compacting peat into the trench and building a slightly raised bund 25-30cm above the current ground surface. In addition, these bunds have 5m long 'finger bunds' constructed using the same technique at approximately 25m spacing to prevent flow along the bund which may lead to erosion. After 1-2 years it is anticipated that the bund will have subsided close to current ground level and therefore will not appear as a prominent feature on the bog surface.



Figure 2.3 Example of contour bund constructed at Knockacoller Bog SAC, Co. Laois

Contour bunds are most effective where there is cracking or slumping in the upper layers of the peat as the re-compacted trench assists in sealing up these cracks and slows the flow rate through the peat, supporting a higher water table behind the bund. The key issue with this technique is that the extent of the impact extending back into the bog depends on the hydraulic gradient (which is closely correlated to surface slope). As a result, the extent of impact from such bunds is likely to be extremely limited where the surface slope at the margins is steep. This method is best suited to sites with a relatively gentle slope towards the margins or as a means of effectively blocking a dense network of shallow surface drains on the high bog. Ground conditions will play an important factor in whether the bund can be constructed in such circumstances, therefore this method is most effective on drier sites where machines can operate safely and effectively.

Action 2.3: Assess the feasibility of contour bunding on the high bog at Moneybeg and Claireisland Bogs SAC

Contour bunding has not been proposed for Moneybeg and Claireisland Bogs SAC. The potential for this measure is being explored through the current restoration plan review process. Proposals should be informed by monitoring the response from this measure at other restoration sites.

2.5 Cell bunding

Cell bunding involves the creation of individual cells, consisting of a cutoff walls extending into the peat substrate and protruding above the ground surface to create a water table close to or slightly above the ground surface (maximum depth typically 10-20cm). The approach permits the interception of laterally flowing groundwater by low permeability cutoff walls, while the surface bunds prevent lateral discharge of surface water; this also encourages recharge to the underlying water table, helping contribute to the water balance, while also maintaining an elevated water table in those areas up gradient of standing water. Due to topographic variable the depth of water will also vary significant resulting in significant ecological diversity across the bunded area.

Cell bunds are typically constructed by excavating a trench 1.0-1.5m deep, recompacting the excavated peat into the trench and constructing a bund 0.5-0.6m high above the ground surface (Figure 2.4). Water level control structures (pipes or overflow weirs) are incorporated into these cells as a means to regulate water levels and evenly distribute water across the site.



Figure 2.4 Example of existing cell bund constructed at Cloncrow Bog NHA

Action 2.4: Assess the feasibility of cell bunding at Moneybeg and Claireisland Bogs SAC

Cell bunding has not yet been proposed for Moneybeg and Claireisland Bogs SAC; however, there is a current ongoing review of the restoration plan to determine the potential for implementing enhanced measures such as cell bunding. Some cutover areas appear to have suitable conditions to allow implementation of this measure. Proposals should be informed by monitoring the response from this measure at other restoration sites.

2.6 General site management

In addition to the proposed measures, it is important that the restoration plan contributes to improving general site management. This includes considering issues such as:

- Fire prevention and response
- Management of littering/fly-tipping

Burning of the high bog can result in significant damage to a raised bog by removing peat-forming vegetation which reduces the capacity of the peat to retain water. This causes much more rapid surface run-off and therefore can result in more widespread drying out and increased peak flows in surrounding streams. Both Moneybeg Bog and Clareisland Bog have been damaged on several occasions through burning. There is evidence of at least two significant fires on Moneybeg Bog in recent years, the first occurred in 2003 and the second in 2010 (Crowley & Crushell, 2015a). There have also been recent fires at Clareisland Bog with fires affecting a small proportion of the high bog reported in 2014 and 2012, with more extensive fires occurring in 2010 and 2003 (Crowley & Crushell, 2015b).

At both Moneybeg Bog and Clareisland Bog there are also high levels of illegal dumping on the cutover in parts of the site particularly close to tracks/access points (NPWS, 2015b). Depending on the nature of the material dumped this can lead to pollution in surrounding areas.

Action 2.5: Prepare a fire prevention and control plan for Moneybeg and Clareisland Bogs SAC in consultation with local stakeholders.

It is proposed that a fire prevention plan is developed for Moneybeg and Clareisland Bogs SAC to identify past occurrences of fires, the likely causes and develop an effective plan to prevent fires in future as well as an appropriate response should a fire occur in the future. Issues such as fire prevention and management of littering/fly-tipping also need to be addressed as part of a wider strategy of raising public awareness on the importance of these habitats.

3 Drainage Management Plan

One issue that can cause concerns, particularly for local stakeholders, relates to whether restoration may result in increased flooding in the surrounding area. In many instances bog restoration has the opposite effect by returning more natural hydrological conditions whereby flow is attenuated and reaches the surrounding watercourses more slowly than when drains were present. This is evident at bogs such as Killyconny Bog SAC (000006) where extensive restoration has been carried out on cutover bog and there have been no adverse impacts on adjoining agricultural land.

Nonetheless, many individuals may remain unconvinced on these issues until several years after restoration has taken place. Therefore, in order to provide reassurance, an integrated drainage management plan for the bog and its surroundings has been developed as part of this restoration plan. The drainage management plan will be intended to support the conservation objectives for Moneybeg and Claireisland Bogs SAC by ensuring that the drainage network can be maintained without impacting on the conservation objectives. The plan assesses instances existing impediments to the effective management of the drainage network (e.g. undersized culverts or channels) and provides recommendations in relation to remedial works and maintenance works going forward. Implementation of such measures will ensure that the risk of flooding will be significantly reduced.

Action 3.1: Implement the actions of the Drainage Management Plan for Moneybeg and Claireisland Bogs SAC in conjunction with local stakeholders.

Developing this plan will require input from local stakeholders to ensure that Required actions can be implemented.

4 Community Benefits

Through consultation with the local community and other stakeholders it will be possible to develop ideas for maximising socio-economic benefits for the local community through restoration. These might include building or improving existing facilities, where appropriate (i.e., tracks, board walks, bog bridges), encouraging the creation of small tourism enterprises, promoting the benefits to human health and well-being and enhancing the value of the site as an educational resource. There are many cases where local communities, including local businesses, are actively involved in or supporting the conservation and restoration of raised bogs across the country. Examples of this are found at Abbeylax Bog (Co. Laois), Carrowmagappul Bog SAC (Co. Galway), Girley Bog Natural Heritage Area (NHA) (Co. Meath), Lodge Bog (Co. Kildare) and Scohaboy Bog NHA (Co. Tipperary).

Moneybeg and Clareisland Bogs offer potential for recreation and amenity; there are many tracks and roadways around both bogs, including a council owned track at Clareisland Bog. There is potential for investment in upgrading, expanding and maintaining these tracks as access routes for amenity and recreation subject to local community desire to explore these options. Any proposed amenity facilities will need to be implemented in a way that does not impact on the site-specific conservation objectives for the site.

Apart from immediate economic benefits, the restoration of raised bogs can provide many other benefits to the wider community, such as provision of clean water, flood attenuation and water flow regulation, preservation of archaeological artefacts and other sources of historical knowledge and, not least, helping Ireland reduce its national greenhouse gas emissions and, therefore, helping to combat climate change.

Action 4.1: Optimise the community benefits of the restoration plan.

As the restoration plan is further developed and implemented, opportunities to improve the recreation and amenity value of the bog and surrounding areas and promote local initiatives, while protecting and enhancing its natural values, will be explored by and with the local community. Promoting community involvement in the long-term management of the site both during and after restoration measures are carried out, will be encouraged.

5 Restoration Plan Implementation

5.1 Preparatory

Prior to implementation of the restoration plan several preparatory actions are required before construction of restoration measures can commence. A summary of these preparatory actions is outlined below:

- Hydrological characterisation – collation of existing hydrological data, hydrological surveys, instrumentation with monitoring data (where necessary);
- Review of proposed restoration measures in line with best practice at the time of implementation (including exploring opportunities to implement enhanced measures);
- Detailed ecological surveys (primarily comprising surveys of cutover areas, but where necessary also includes high bog areas e.g., if ecotopes have not been surveyed in many years);
- Landownership Investigations (investigations into ownership, turbary rights etc.);
- Stakeholder consultation and community engagement (meeting with stakeholders to outline restoration plans and consider any concerns raised by the local community);
- Compensation/land acquisition (compensation or acquisition of lands required to implement

the required restoration measures on private lands);


- Appropriate Assessment Screening;
- Compilation of tender/construction documents including preparation of health and safety file;
- Surveying and setting out of the works;
- Implementation of restoration measures (including construction supervision and contract administration);
- Post-works inspections and preparation of as-built survey information;
- Update of restoration plan to outline works completed and remaining works required in future.

5.2 Progress to date


Moneybeg and Clareisland Bogs SAC has been selected as one of the People and Peatlands Project sites. The Peatlands and People LIFE IP (LIFE19 IPC/IE/000007) is a 9.9m EU LIFE Integrated Project, led by Bord na Móna which aims to be Ireland's Climate Action Catalyst by improving the condition of 9,900ha of peatlands. National Parks and Wildlife Service (NPWS) as a joint beneficiary aim to develop and implement comprehensive restoration plans for 15 designated raised bogs including Moneybeg and Clareisland Bogs SAC.

As part of this project, all aspects of the restoration plan (section 2-4) are currently being reviewed and updated using current best practice. The project aims to restore these sites and install a detailed hydrological monitoring network to measure a wide range of ecosystem benefits obtained through the restoration of Moneybeg and Clareisland Bogs SAC, including increased carbon sequestration, biodiversity enhancement, improvements to water quality and regulation of flood flows.

Further updates will be provided to this living document as design decisions are finalized and monitoring equipment is installed. Implementation of this restoration plan will then be progressed through this project.



Map 1 - Moneybeg and Clareisland Bogs SAC Boundary



Map 2 - Moneybeg and Clareisland Bogs SAC Restoration Proposals

6 References

- Crowley W. & Crushell, P. (2015a) Raised Bog Monitoring and Assessment Survey 2015 – Moneybeg Bog – Site Report. National Parks and Wildlife Service, Department of Arts, Heritage and Gaeltacht, Dublin, Ireland.
- Crowley W. & Crushell, P. (2015b) Raised Bog Monitoring and Assessment Survey 2015 – Clareisland Bog – Site Report. National Parks and Wildlife Service, Department of Arts, Heritage and Gaeltacht, Dublin, Ireland.
- Fernandez, F., Connolly K., Crowley W., Denyer J., Duff K. & Smith G. (2014) Raised Bog Monitoring and Assessment Survey 2013. Irish Wildlife Manuals, No. 81. National Parks and Wildlife Service, Department of Arts, Heritage and Gaeltacht, Dublin, Ireland.
- Kelly, L., Doak, M. & Dromey, M. (1995) Raised Bog Restoration Project: An Investigation into the Conservation and Restoration of Selected Raised Bog Sites in Ireland. Part 1 Summary Reports. National Parks & Wildlife Service, Department of Environment, Heritage and Local Government, Dublin.
- Kelly, L. & Schouten, M.G.C. (2002) Vegetation. In: Schouten, M.G.C. (ed.), Conservation and restoration of raised bogs: geological, hydrological and ecological Studies. Dúchas – The Heritage Service of the Department of the Environment and Local Government, Ireland; Staatsbosbeheer, the Netherlands; Geological Survey of Ireland, Dublin. pp. 110-169.
- Mackin, F., Flynn, R, Barr, A & Fernandez-Valverde, F. (2017b) Use of geographical information system-based hydrological modelling for development of a raised bog conservation and restoration programme. *Ecological Engineering*, 106(Part A); pp. 242-252.
- Mackin, F., Barr, A., Rath, P., Eakin, M., Ryan, J., Jeffrey, R. & Fernandez Valverde, F. (2017a) Best practice in raised bog restoration in Ireland. *Irish Wildlife Manuals*, No. 99. National Parks and Wildlife Service, Department of Culture, Heritage and the Gaeltacht, Ireland.
- NPWS (2015a) Moneybeg and Clareisland Bogs SAC (site code 002340) Conservation objectives. National Parks and Wildlife Service, Ireland. (http://www.npws.ie/sites/default/files/protected-sites/conservation_objectives/CO002340.pdf)
- NPWS (2015b) Moneybeg and Clareisland Bogs SAC (site code 002340) Conservation objectives supporting document - raised bog habitats. National Parks and Wildlife Service, Ireland. ([http://www.npws.ie/sites/default/files/publications/pdf/Moneybeg%20and%20Clareisland%20Bogs%20SAC%20\(002340\)%20Conservation%20objectives%20supporting%20document%20-%20Raised%20Bog%20habitats%20\[Version%201\].pdf](http://www.npws.ie/sites/default/files/publications/pdf/Moneybeg%20and%20Clareisland%20Bogs%20SAC%20(002340)%20Conservation%20objectives%20supporting%20document%20-%20Raised%20Bog%20habitats%20[Version%201].pdf))
- Regan, S., Swenson, M., O'Connor, M. & Gill, L. (2020). Ecohydrology, Greenhouse Gas Dynamics and Restoration Guidelines for Degraded Raised Bogs. A report prepared for the Environmental Protection Agency, Ireland.
- Smith, G.F. & Crowley, W. (2020) The habitats of cutover raised bog. Irish Wildlife Manuals, No. 128. National Parks and Wildlife Service, Department of Housing, Local Government and Heritage, Ireland.

Glossary & Acronyms

| | |
|---------------------------|---|
| ACTIVE RAISED BOG (ARB) | Areas of uncut raised bog where the conditions are right for peat to continue to form, and where species of plants and animals typical to intact bogs can thrive. ARB is listed as a priority habitat in Annex I of the Habitats Directive. |
| ANNEX I | Annex I of the EU Habitats Directive lists natural habitats types of Community interest whose conservation requires the designation of SACs. |
| ANNEX II | Annex II of the EU Habitats Directive lists animal and plant species of Community interest whose conservation requires the designation of SACs. |
| BIODIVERSITY | A general term used to describe all aspects of biological diversity including the number of species present in a given environment, the genetic diversity present within a species and the number of different ecosystems present within a given environment. |
| BOG WOODLAND | Woodland formed on a wet peaty substrate, with permanently high groundwater level. The water is poor in nutrients (ombrotrophic) and the ground surface has high cover of bog moss species, with active peat accumulation taking place. Bog Woodland is listed as a priority habitat in Annex I of the Habitats Directive. It differs from dry woodland on bog where peat accumulation is not taking place. |
| BUNDING | An impervious embankment of material (peat or other) that provides a barrier to retain water behind it. |
| CARBON SEQUESTRATION | The capture and long-term storage of atmospheric carbon dioxide, including that accumulated by a bog or fen. |
| CATCHMENT | An area of land contributing water that drains to a defined point. The term river catchment refers to the area of land that drains into a particular river system and is synonymous with the term drainage basin or watershed. |
| CUTOVER | Areas of bog that have been previously cut (by hand or by mechanical means), although not down to the underlying inorganic substrate. Cutover areas normally consist of a mosaic of cut areas, face banks, pools, drainage ditches, uncut areas of peat, scrub, grassland etc. |
| DEGRADED RAISED BOG (DRB) | The area of high, uncut bog which has been damaged by human activities but which could be restored to active raised bog again through restoration measures within a period of 30 years. It is listed in Annex I of the Habitats Directive. |
| ECOLOGY | The study of the interactions between organisms, and their physical, chemical and biological environment. |
| ECOSYSTEM SERVICES | Humankind benefits from a multitude of resources and processes that are supplied by ecosystems. Collectively, these benefits are known as ecosystem services and include products like clean drinking water and processes such as the decomposition of wastes. |
| EROSION | The processes whereby the materials of the earth's crust are dissolved, or worn away and simultaneously moved from one place to another by natural processes which include weathering, solution, corrosion and transportation. |

| | |
|---|--|
| EVAPOTRANSPIRATION | Water loss to the atmosphere from soil and other surfaces (evaporation) and vegetation (transpiration). |
| FACEBANK | Areas at the edge of the high bog where peat cutting has taken place. This is an ecotope that is highly degraded and absent of typical <i>Sphagnum</i> species. |
| FAUNA | Animal life. |
| FAVOURABLE CONSERVATION CONDITION | This is the condition of a habitat or species considered to be favourable at site level. Favourable conservation condition is defined by site-specific conservation objectives (SSCOs). The maintenance of habitats and species within sites at favourable condition will contribute to the maintenance of favourable conservation status of those habitats and species at a national level. |
| FAVOURABLE CONSERVATION STATUS | According to the Habitats Directive the conservation status of a natural habitat will be taken as "favourable" when: its natural range and areas it covers within that range are stable or increasing, and the specific structure and functions which are necessary for its long term maintenance exist and are likely to continue to exist for the foreseeable future, and the conservation status of its typical species is favourable. |
| FLORA | Plant life. |
| FLOW ATTENUATION | Slowing flow of water out of an area. This is a common method for reducing risk of flood in urban areas whereby diversion channels store water in attenuation ponds. Intact peatlands typically offer natural flow attenuation through slowing flow as a result of higher storage capacity and increased hydraulic roughness, while degraded peatlands are much less effective at attenuating flow as the peat is dried out encouraging overland flow. |
| HABITAT | Refers to the environment defined by specific abiotic and biotic factors, in which a species lives at any stage of its biological cycle. In general terms it is a species' home. |
| HABITATS DIRECTIVE | Council Directive 92/43/EEC of 21 May 1992 on the conservation of natural habitats and of wild fauna and flora. |
| HEAD | Hydrological term which is a measure of the height to which water can raise itself above an arbitrary given level or datum. |
| HIGH BOG | The area of bog which has not previously been cut. |
| HYDROLOGICAL PROCESSES | The movement of water through a catchment area including freshwater and seawater inputs, water level changes and drainage mechanisms which are all influenced by the underlying geology. |
| LAGG | A term used to describe the natural habitat that occurs in the transitional zone between the bog and the mineral soil around a raised bog. Few intact lagg |

| | |
|-----------------------------|--|
| | zones remain around raised bogs in Ireland as they are typically the first location to be damaged by drainage. |
| LIDAR | A remote sensing technology that measures vertical surface elevation by illuminating a target with a laser and analysing the reflected light usually obtained using a low-flying aeroplane. This provides detailed information on the surface elevations across an area. |
| LIFE | An EU financial instrument supporting environmental and nature conservation projects throughout the EU. |
| MARGINAL DRAIN | Drains on the margins of a raised bog typically on cutover for the purpose of draining spread-grounds to facilitate turf-cutting. |
| MICROTOPOGRAPHY | Variations in elevation at a relatively small scale. Generally the higher points are no more than a metre higher than the low points, and only a couple of metres across. On a high bog this consists of hummocks, hollows, pools, flats and lawns. |
| MINEROTROPHIC | Refers to soils and vegetation whose water supply comes mainly from streams or springs. This water has flowed over or through rocks or other minerals, often acquiring dissolved chemicals which raise the nutrient levels and reduce the acidity. |
| NATURAL HERITAGE AREA (NHA) | These are conservation areas designated for protection under The Wildlife (Amendment) Act 2000. NHAs are considered important for the habitats present or which holds species of plants and animals whose habitat needs protection. |
| NPWS | National Parks and Wildlife Service. |
| OMBROTROPHIC | Refers to a type of peatland that receives all of its water and nutrient from precipitation falling directly on its surface. |
| PIEZOMETER | A piezometer is a device used to measure head. In the case of groundwater a piezometer will provide head at a given point. |
| PEAT-FORMING HABITAT | These are habitats where peat is actively forming. It includes typical ombrotrophic raised bog vegetation as well as lagg or fen vegetation that indicate that peat is actively forming. |
| PRIORITY HABITAT | A subset of the habitats listed in Annex I of the EU Habitats Directive. These consist of habitats which are in danger of disappearance and whose natural range mainly falls within the territory of the European Union. These habitats are of the highest conservation status and require measures to ensure that their favourable conservation status is maintained. |
| RAISED BOG | Rain-fed peatland ecosystems that develop primarily in areas with topographic depressions, where drainage may be impeded by a high groundwater table, or by low permeability of the underlying substrata such as clay. Peat accumulation, over time, elevates the ground surface above surrounding areas to form a raised dome. |
| RESTORATION ZONE | A specified area within a site where restoration measures have been proposed. Restoration zones have been defined for each raised bog SAC based on factors including hydrological conditions, existing and expected habitats following restoration. This allows restoration measures for each raised bog SAC to be split into manageable units. |
| SITE-SPECIFIC | |

| | |
|------------------------------|---|
| CONSERVATION OBJECTIVE | A site-specific conservation objective aims to define the favourable conservation condition of a habitat or species at site level. The maintenance of habitats and species within sites at favourable condition will contribute to the maintenance of favourable conservation status of those habitats and species at a national level. |
| SPECIAL AREA OF CONSERVATION | Area designated for the conservation of habitats and/or species under the Habitats Directive. |
| SPREAD-GROUNDS | Area where turf is spread after cutting to dry out, typically drained cutover bog or agricultural areas adjacent to the high bog. |
| STATUTORY NATURE RESERVE | A Statutory Nature Reserve is an area of nature conservation interest that has been designated by Ministerial Order under the Wildlife Act, 1976. |
| SUBSIDENCE | Term referring to the sinking of land resulting from natural activity or human activity. Within peat subsidence occurs due to loss of water for example as a result of drainage. |
| TILL | Geological term referring to unsorted material deposited by glacial ice and showing no stratification. It is often referred to as boulder clay. |
| TOPOGRAPHY | The arrangement of the physical features of an area. |